

# Whoosh User Sentiment Analysis on Social Media Using Word2Vec and the Best Naïve Bayes Probability Model

Muhammad Dinan Islamanda <sup>1)\*</sup>, Yuliant Sibaroni<sup>2)</sup>

<sup>1,2)</sup> School of Computing, Telkom University, Indonesia

<sup>1)</sup> [dinanislamanda@student.telkomuniversity.ac.id](mailto:dinanislamanda@student.telkomuniversity.ac.id), <sup>2)</sup> [yuliant@telkomuniversity.ac.id](mailto:yuliant@telkomuniversity.ac.id)

**Submitted** : Jun 10, 2024 | **Accepted** : Jun 28, 2024 | **Published** : Jul 1, 2024


**Abstract:** By using the Twitter microblogging feature, users can post short tweets with limited characters that express their thoughts and opinions regarding a matter. The newest transportation in Indonesia, a high-speed train namely Whoosh is one of the things that Twitter users responded to. This latest transportation has led to the emergence of opinions from the Indonesian people which are shared publicly in various media, one of which is social media. Therefore, to make it easier for business people or companies to understand public opinion regarding service improvements in the future, sentiment analysis on social media is needed to determine user opinions regarding high-speed train transportation. In this research, sentiment analysis of high-speed train users will be carried out on social media Twitter using Word2Vec and Naïve Bayes as classification methods. In this research, a comparison of Naïve Bayes models will also be carried out to find out the best Naïve Bayes method opportunity model. Simultaneously, the Word2vec feature extraction method was chosen because Word2Vec can be used to improve model performance and increase the accuracy of sentiment classification. This research found that the Word2Vec Skip-Gram model outperformed the Word2Vec CBOW model. The best model obtained was the use of the Gaussian Naïve Bayes and Word2Vec Skip-Gram models with an accuracy score of 77.18%, precision 70.35%, recall 76.09%, and f1-score 73.10%.

**Keywords:** high-speed train, naïve bayes, sentiment analysis, twitter, word2vec

## INTRODUCTION

By using the Twitter microblogging feature, users can post short tweets with limited characters that express their thoughts and opinions regarding a matter (Malik et al., 2019). The newest transportation in Indonesia, a high-speed train namely Whoosh is one of the things that Twitter users responded to. Whoosh travels from Jakarta to Bandung and vice versa. High-speed trains have technological advances compared to conventional trains which are able to shorten travel time, especially for medium distance travel (Lestari et al., 2018). However, this transportation raises many opinions from the public. According to Dhea, a resident of Bandung, high-speed train transportation must have affordable prices and facilities commensurate with those offered (Awla Rajul, 2023). Affordable and efficient mass transportation is very important for the survival of society (Gershon, 2005). Therefore, to make it easier for business people or companies to understand public opinion regarding service improvements in the future, sentiment analysis on social media is needed to determine user opinions regarding high-speed train transportation.

\*name of corresponding author



Many studies discussing sentiment analysis use classification methods and various feature extraction methods. Word2Vec can produce a high f1-score value in Indonesian news categorization using the Naïve Bayes algorithm with an average f1-score value of 90% (Santoso et al., 2018). In e-wallet sentiment analysis research using Naïve Bayes and N-Gram, the use of 2 grams made the data tested better than before. Obtained 94.90% accuracy with the Naïve Bayes algorithm for OVO and 94.70% accuracy for DANA (Kristiyanti et al., 2020). In sentiment analysis research using Random Forest and Word2Vec, the accuracy results using Word2Vec were 86.87%, higher than using Bag-of-Word and TF-IDF with accuracy of 83.49% and 84.49% (Hitesh et al., 2019).

Applying Naïve Bayes machine learning classification to sentiment analysis obtained quite good accuracy compared to Random Forest and SVM. The proposed algorithm performs better for higher volume tweets (Shamantha et al., 2019). Naïve Bayes provides accuracy results of 80.9% compared to KNN 75.58% and SVM 63.88% in sentiment analysis for Twitter analysis of the 2019 Presidential Candidates of the Republic of Indonesia (Wongkar & Angdresey, 2019).

Naïve Bayes has several models and each model has its characteristics. Multinomial and Bernoulli Naïve Bayes classifiers are suitable for discrete data. The difference is, when classifying test documents, Multinomial Naïve Bayes works by tracking several events, while Bernoulli Naïve Bayes uses binary event information, ignoring the number of events (Schütze et al., 2008). Complement Naïve Bayes is suitable for imbalanced datasets and this classifier improves classification accuracy by using data from all classes except the class on which it is focused (Sato et al., 2011). When dealing with continuous data, it is commonly assumed that each class's continuous values are distributed using a Gaussian distribution. For instance, the continuous attribute  $x$  is present in the training set. The mean and variance  $x$  are computed for each class after the data has been divided into segments based on class (Gayathri & Sumathi, 2016).

From previous research, Naïve Bayes is a classification method that is quite good at classifying sentiment among other methods and Word2Vec can improve performance results in classification algorithms. In this research, sentiment analysis of high-speed train users will be carried out on social media Twitter using Word2Vec and Naïve Bayes as classification methods. In this research, a comparison of Naïve Bayes models will also be carried out to find out the best Naïve Bayes method opportunity model for analyzing the sentiment of high-speed train users on Twitter social media using Word2vec feature extraction. Simultaneously, the Word2vec feature extraction method was chosen because Word2Vec can be used to improve model performance and increase the accuracy of sentiment classification.

## LITERATURE REVIEW

The research topic regarding sentiment analysis using machine learning classifiers has been carried out previously. Sentiment analysis research on tweets data using Naïve Bayes, SVM, and Random Forest classification. The application of Naïve Bayes and SVM machine learning classification to sentiment analysis obtained quite good accuracy compared to Random Forest. Increased accuracy also occurs with the use of extraction features (Shamantha et al., 2019).

Sentiment analysis research on transportation has been carried out on KAI (Indonesian Railway) using SVM and TF-IDF. Tweets containing user opinions on Twitter regarding the services provided by KAI were used in this research. The classification results using the OAA Multiclass SVM method in this study used different weighting features. The unigram TF-IDF model in conjunction with the OAA Multiclass SVM with gamma 0.7 yields the highest accuracy of 80.59 (Fitriana & Sibaroni, 2020).

Additionally, a number of studies employing the Naïve Bayes method have been conducted. Sentiment analysis research on KFC product reviews on Twitter and YouTube was carried out using Naïve Bayes. The application of the Naïve Bayes algorithm obtained quite good accuracy of 85.48% for data before endorsement and 86.48% for data after endorsement (Ramdhani et al., 2018). Sentiment analysis research on customer satisfaction with Gojek and Grab Indonesia using Naïve Bayes. The data used is the result of collecting tweets based on keywords about Gojek and Grab in Indonesian Language. Obtained accuracy of 72.33% with 73.95% and 73.24% of recall and precision on average (Sari et al., 2019).

\*name of corresponding author



This is anCreative Commons License This work is licensed under a Creative Commons Attribution-NonCommercial 4.0 International License.

Several studies using the Word2Vec method have also been carried out. Sentiment analysis research on hotel reviews was carried out using the LSTM and Word2Vec methods. There is a comparison of the Word2Vec architecture used in this research. It was found that the best scheme achieved an average accuracy of 85.96%, with Skip-Gram used as the Word2Vec architecture, and with the vector dimension value set to 300 (Muhammad et al., 2021). Comparison of Multinomial and Gaussian Naïve Bayes was carried out in sentiment analysis research on movie reviews using Word2Vec. There is a comparison of testing the number of dimensions in Word2Vec with a total of 300 dimensions being the best model. The Multinomial Naïve Bayes model provides the highest accuracy of 72.23% compared to the Gaussian Naïve Bayes model with an accuracy of 68.72% (Rizal et al., 2022).

From the results of previous studies, the Naïve Bayes classification method is a good method for classifying sentiment among other classification methods such as Random Forest and SVM. The Word2Vec method can also help improve the accuracy of sentiment classification. This research will analyze the sentiment of high-speed train users using Word2Vec and Naïve Bayes. In this research, a comparison of Naïve Bayes models will also be carried out to find out the best Naïve Bayes method opportunity model.

### METHOD

The purpose of this research is to create a sentiment classification system for user feedback on high-speed train transportation, comparing four Naïve Bayes models and the Word2Vec architecture. Figure 1 shows the system design flowchart that is shown below.




Fig. 1 System overview flow chart

#### Dataset

Crawling methods were utilized to obtain the dataset from Twitter for this research. The data that has been crawled is tweet data related to high-speed trains such as 'kereta cepat', 'whoosh', 'KCIC', and 'kereta cepat jakarta bandung' and saved in a CSV file. The dataset used is 12,923 data containing user opinion tweets regarding high-speed train transportation in the Indonesian language.

#### Preprocessing

The data resulting from data crawling will be pre-processed so that the data becomes clean data and is easier to carry out sentiment classification. This stage consists of several processes. Table 1 shows several stages in data preprocessing. Stopword Removal and Tokenization stages using the NLTK library. The indoNLP library is used in the Replace Slang Words, Remove Elongation, and Replace Emoji stages, while the Stemming stage uses the Sastrawi library.

\*name of corresponding author




Table 1. Example of Preprocessing Text Result

Stages	Explanation	Result
Actual Text	Example of user tweets	Kemarin sudah mencoba kereta cepat, kagumm bgt. Pemandangan yg keren dan indah 😊. Perjalanan ga berasa lama tiba tiba udh sampe #whoosh
After Case Folding	Change all letters to lowercase	kemarin sudah mencoba kereta cepat, kagumm bgt. pemandangan yg keren dan indah 😊. perjalanan ga berasa lama tiba tiba udh sampe #whoosh
After Stopword Removal	Removal of all stopwords	kemarin mencoba kereta cepat, kagumm bgt. pemandangan yg keren indah 😊. perjalanan ga berasa udh sampe #whoosh
After Replace Slang Words	Change of abbreviated words	kemarin mencoba kereta cepat, kagumm banget. pemandangan yang keren indah 😊. perjalanan enggak berasa sudah sampai #whoosh
After Remove Elongation	Changing words that have elongation	kemarin mencoba kereta cepat, kagum banget. pemandangan yang keren indah 😊. perjalanan enggak berasa sudah sampai #whoosh
After Emoji to Word	Turns an emoji into a word	kemarin mencoba kereta cepat, kagum banget. pemandangan yang keren indah !wajah_gembira!. perjalanan enggak berasa sudah sampai #whoosh
After Cleansing	Removal of URLs, numbers, symbols, usernames, and punctuation	kemarin mencoba kereta cepat kagum banget pemandangan yang keren indah wajah gembira perjalanan enggak berasa sudah sampai
After Stemming	Convert a word to its base word	kemarin coba kereta cepat kagum banget pandang yang keren indah wajah gembira jalan enggak asa sudah sampai
After Tokenization	Breaking tweet text into tokens	['kemarin', 'coba', 'kereta', 'cepat', 'kagum', 'banget', 'pandang', 'yang', 'keren', 'indah', 'wajah', 'gembira', 'jalan', 'enggak', 'asa', 'sudah', 'sampai']

### Word2Vec Word Embedding

In Natural Language Processing, word embedding is a crucial step that involves taking unlabeled text data and extracting syntactic and semantic features from it. (Li & Yang, 2018). Word2Vec word embedding is used in this research and is carried out after the data preprocessing process. Word2Vec converts words into vectors according to several parameters, including vector dimensions and window size. Similar words are typically grouped in the same block and have similar vector values (Jatnika et al., 2019). Continuous Bag of Words (CBOW) and Skip-Gram are two architectures in Word2Vec. In contrast to Skip-Gram architecture which predicts words around the current given word, CBOW architecture predicts current words based on context. The following figure is the Skip-Gram and CBOW architecture.

\*name of corresponding author



This is anCreative Commons License This work is licensed under a Creative Commons Attribution-NonCommercial 4.0 International License.




Fig. 2 Word2Vec Architecture Models

**Split Data**

Following Word2Vec word embedding, the data will be divided into training and testing groups. 90% of the training data and 10% of the testing data make up the 90:10 division ratio. Data division is carried out randomly.

**Cross Validation**

Rerunning the entire procedure k times using distinct training and testing datasets is the goal of the k-fold cross-validation technique. (Saud et al., 2020). The optimal model is then chosen by obtaining the minimum error using a variety of statistical tools for error estimation. This research uses the formula k = 10 fold to calculate k in k-folds. The following figure is the cross validation illustration.





Fig. 3 Cross Validation Illustration

\*name of corresponding author





## Naïve Bayes Model Learning

Naïve Bayes classification is a supervised learning classification algorithm in machine learning. This classification is rooted in the Bayesian theorem by Thomas Bayes in determining probability. These probabilistic models make it possible to capture model uncertainty in principle by specifying probabilities (Parveen & Pandey, 2016). From a classification point of view, the main goal of this classification is to determine the optimal mapping between new data and a set of classifications in a certain problem domain (Yang, 2018). The following is the equation formula for the Naïve Bayes method.

$$P(y_j|x_i) = \frac{P(x_i|y_j) \cdot P(y_j)}{P(x_i)} \quad (1)$$

Where,  $P(y_j|x_i)$  is the probability of category  $j$  when word  $i$  appears,  $P(y_j)$  is the probability of category  $j$  appearing,  $P(x_i|y_j)$  is the probability that word  $i$  is included in category  $j$ ,  $P(x_i)$  is the probability of appearing a word.

The odds in the formula above can be calculated using several assumptions regarding the probability distribution, namely:

a. Multinomial Naïve Bayes

This Naïve Bayes model uses a multinomial model to represent the word distribution in a document. Words are treated as a sequence in documents, and it's thought that every word position is generated separately from the others (Rennie et al., 2003). The Multinomial Naïve Bayes formula is as follows.

$$P(x|C_k) = \frac{(\sum_{i=1}^n x_i)!}{\prod_{i=1}^n x_i!} \prod_{i=1}^n P_{ki}^{x_i} \quad (2)$$

Where,  $P_{ki} := P(x_i|C_k)$ .

b. Gaussian Naïve Bayes

When dealing with continuous data, it is commonly assumed that each class's continuous values are distributed using a Gaussian distribution. For instance, the continuous attribute  $x$  is present in the training set. The mean and variance  $x$  are computed for each class after the data has been divided into segments based on class (Gayathri & Sumathi, 2016). Therefore, the following formula can be used to estimate the probability of a continuous dataset.

$$P(x_i|y) = \frac{1}{\sqrt{2\pi\sigma_y^2}} e^{-\frac{(x_i-\mu_y)^2}{2\sigma_y^2}} \quad (3)$$

c. Bernoulli Naïve Bayes

The Bernoulli Naïve Bayes model is very suitable for performing binary classification (McCallum & Nigam, 1998). Discrete data is also suitable using Bernoulli Naïve Bayes as with Multinomial Naïve Bayes. However, the difference is that Multinomial Naïve Bayes works with the number of events, the Bernoulli model uses binary event information, ignoring the number of events (Schütze et al., 2008). The following is the Bernoulli Naïve Bayes formula.

$$P(x|C_k) = \prod_{i=1}^n P_{ki}^{x_i} (1 - P_{ki})^{(1-x_i)} \quad (4)$$

Where,  $P_{ki}$  is the likelihood that the term  $x_i$  will be generated by class  $C_k$ .

d. Complement Naïve Bayes

Complement Naïve Bayes classifier is a modification of the Multinomial Naïve Bayes classifier and is suitable for imbalanced datasets. This classifier improves classification accuracy by using data from all classes except the class on which it is focused (Sato et al., 2011). Complement Naïve Bayes estimation will be more effective because each class uses a more even amount of

training data per class, thereby reducing bias in weight estimation (Rennie et al., 2003). The Complement Naïve Bayes formula is as follows.

$$l_{CNB}(d) = \operatorname{argmax}_c \left[ \log p(\vec{\theta}_c) - \sum_i f_i \log \frac{N_{\bar{c}i} + \alpha_i}{N_{\bar{c}} + \alpha} \right] \quad (5)$$

Where  $N_{\bar{c}i}$  is the quantity of instances of the word  $i$  in documents from classes other than  $c$ ,  $N_{\bar{c}}$  is the total count of words that appear in classes other than  $c$ , and  $\alpha_i$  and  $\alpha$  are smoothing parameters.

### Evaluation

Using a confusion matrix, the constructed model will be assessed to ascertain its performance. Confusion Matrix is a machine learning visual assessment tool, the actual class results are represented by the rows, and the predicted class results are represented by the columns (Xu et al., 2020). The following are some of the most given sizes.

Accuracy, this metric is used to calculate the proportion of all correctly predicted cases (Deng et al., 2016).

$$Accuracy = \frac{TP+TN}{TP+FP+TN+FN} \quad (6)$$

Precision, this measurement is used to determine the level of accuracy of predictions for certain classes (Deng et al., 2016).

$$Precision = \frac{TP}{TP+FP} \quad (7)$$

Recall, this measurement is used to identify examples of a particular class from a data set (Deng et al., 2016).

$$Recall = \frac{TP}{TP+FN} \quad (8)$$

F1-Score, a measurement of the harmonic mean between precision and recall (Deng et al., 2016).


$$F1 - Score = \frac{2 \times Precision \times Recall}{Precision+Recall} \quad (9)$$

There are 4 values in the confusion matrix, namely True Positive (TP) the positive (Actual) number which is categorized correctly as positive, True Negative (TN) the negative (Actual) number which is correctly categorized as negative, False Positive (FP) the negative (actual) number which are incorrectly categorized as positive, and False Negative (FN) the number of (actual) positives which are incorrectly categorized as negative (Zeng, 2020). These values are defined based on the following confusion matrix in Table 2.

Table 2. Confusion Matrix

		Actual Class	
		Positive	Negative
Predicted Class	Positive	TP	FP
	Negative	FN	TN

\*name of corresponding author



## RESULT

This research uses a dataset of 12,923 with a data composition of 7,651 negative sentiments and 5,272 positive sentiments. The preprocessed data is followed by feature extraction using Word2Vec to implement the processed data. In this study, an assessment was finished using the Naïve Bayes classification and Word2Vec Word Embedding by comparing four Naïve Bayes probability models (Multinomial Naïve Bayes, Bernoulli Naïve Bayes, Gaussian Naïve Bayes, and Complement Naïve Bayes) and also the Word2Vec architectural model (CBOW and Skip-Gram) after the modeling stage to find the most optimal accuracy results. Evaluations of recall, accuracy, precision, and f1-score are included in the test results, are presented in Table 3 and Table 4.

Table 3. CBOW Result

Naïve Bayes Model	Accuracy	Precision	Recall	F1-Score
Multinomial Naïve Bayes	73.70%	78.76%	48.57%	60.09%
Complement Naïve Bayes	74.24%	67.13%	72.10%	69.53%
Bernoulli Naïve Bayes	74.24%	67.25%	71.72%	69.42%
Gaussian Naïve Bayes	75.87%	70.09%	71.15%	70.62%

Table 4. Skip-Gram Result

Naïve Bayes Model	Accuracy	Precision	Recall	F1-Score
Multinomial Naïve Bayes	75.25%	82.85%	49.52%	61.99%
Complement Naïve Bayes	76.10%	68.10%	77.79%	72.63%
Bernoulli Naïve Bayes	75.94%	67.70%	78.36%	72.64%
Gaussian Naïve Bayes	77.18%	70.35%	76.09%	73.10%

Based on the two tables above, it was found that using the Word2Vec Skip-Gram and Gaussian Naïve Bayes models produced the best results with an accuracy of 77.18%.

## DISCUSSIONS

The Gaussian Naïve Bayes model and the Word2Vec Skip-Gram model obtained the most optimal results with accuracy of 77.18%, precision of 70.35%, recall of 76.09%, and f1-score of 73.10% with the confusion matrix, as can be seen in Table 5. These results are based on the evaluation results using the four Naïve Bayes models and the Word2Vec architecture model (Skip-Gram and CBOW).

Table 5. Confusion Matrix Result

		Actual Class	
		Positive	Negative
Predicted Class	Positive	401	169
	Negative	126	597

Table 5 shows that, in comparison to Word2Vec CBOW and other Naïve Bayes models, Gaussian Naïve Bayes and Word2Vec Skip-Gram yield more accurate results for high-speed train user sentiment. These are the values of the confusion matrix that resulted.

1. True Positive (TP) totaled 401, wherein 401 data that the model both predicted and actually classified as positive.
2. True Negative (TN) totaled 597, wherein 597 data that the model both predicted and actually classified as negative.
3. The model classified 169 data that it had incorrectly predicted as positive but were actually negative, yielding a total of 169 False Positives (FP).
4. The model classified 126 data that it had incorrectly predicted as negative but were actually positive, yielding a total of 126 False Negatives (FN).

\*name of corresponding author



This is an Creative Commons License This work is licensed under a Creative Commons Attribution-NonCommercial 4.0 International License.



## CONCLUSION

In research on high-speed train user sentiment analysis using the Naïve Bayes algorithm and Word2Vec word embedding, four variants of the Naïve Bayes model were compared in each test. Testing also compares the performance of Skip-Gram and CBOW Word2Vec models. The use of Naïve Bayes and Word2Vec models influences performance results. The test results show that the Gaussian Naïve Bayes model obtains better performance results than the other three Naïve Bayes models.

However, the use of the Word2Vec Skip-Gram model provides better performance than the Word2Vec CBOW model. The Skip-Gram model provides 2 percent superior accuracy and higher recall results compared to the CBOW model.

In this research, the best combination of Naïve Bayes and Word2Vec methods was found, namely the use of the Gaussian Naïve Bayes and Word2Vec Skip-Gram models which obtained accuracy results of more than 77%. This combination also gets precision, recall and f1-score results of 70.35%, 76.09%, and 73.10%.

Suggestions for further research, to produce better results could be to use a more complex classification model. Other word embedding methods can also be used to compare the Word2Vec method to find out which method is better.

## REFERENCES

- Awla Rajul. (2023). Kritik dan Saran dari Calon Penumpang Kereta Cepat Jakarta Bandung. *BandungBergerak.Id*. <https://bandungbergerak.id/article/detail/15785/kritik-dan-saran-dari-calon-penumpang-kereta-cepat-jakarta-bandung>
- Deng, X., Liu, Q., Deng, Y., & Mahadevan, S. (2016). An improved method to construct basic probability assignment based on the confusion matrix for classification problem. *Information Sciences*, 340–341, 250–261. <https://doi.org/https://doi.org/10.1016/j.ins.2016.01.033>
- Fitriana, D. N., & Sibaroni, Y. (2020). Sentiment analysis on kai twitter post using multiclass support vector machine (svm). *Jurnal RESTI (Rekayasa Sistem Dan Teknologi Informasi)*, 4(5), 846–853.
- Gayathri, B. M., & Sumathi, C. P. (2016). An Automated Technique using Gaussian Naïve Bayes Classifier to Classify Breast Cancer. *International Journal of Computer Applications*, 148(6), 16–21. <https://doi.org/10.5120/ijca2016911146>
- Gershon, R. R. M. (2005). Public transportation: Advantages and challenges. *Journal of Urban Health*, 82(1), 7–9. <https://doi.org/10.1093/jurban/jti003>
- Hitesh, M., Vaibhav, V., Kalki, Y. J. A., Kamtam, S. H., & Kumari, S. (2019). Real-Time Sentiment Analysis of 2019 Election Tweets using Word2vec and Random Forest Model. *2019 2nd International Conference on Intelligent Communication and Computational Techniques (ICCT)*, 146–151. <https://doi.org/10.1109/ICCT46177.2019.8969049>
- Jatnika, D., Bijaksana, M. A., & Suryani, A. A. (2019). Word2Vec Model Analysis for Semantic Similarities in English Words. *Procedia Computer Science*, 157, 160–167. <https://doi.org/https://doi.org/10.1016/j.procs.2019.08.153>
- Kristiyanti, D. A., Putri, D. A., Indrayuni, E., Nurhadi, A., & Umam, A. H. (2020). E-Wallet Sentiment Analysis Using Naïve Bayes and Support Vector Machine Algorithm. *Journal of Physics: Conference Series*, 1641(1), 012079. <https://doi.org/10.1088/1742-6596/1641/1/012079>
- Lestari, F., Purba, A., & Zakaria, A. (2018). Komparasi Pembangunan Kereta Cepat di Indonesia Dengan Kereta Cepat di Negara Lain dari Sudut Pandang Ekonomi. *Prosiding Semnas SINTA FT UNILA Vol. 1 Tahun 2018*, 1(1), 266–272.

\*name of corresponding author



This is anCreative Commons License This work is licensed under a Creative Commons Attribution-NonCommercial 4.0 International License.

- Li, Y., & Yang, T. (2018). Word Embedding for Understanding Natural Language: A Survey. In S. Srinivasan (Ed.), *Guide to Big Data Applications* (pp. 83–104). Springer International Publishing. [https://doi.org/10.1007/978-3-319-53817-4\\_4](https://doi.org/10.1007/978-3-319-53817-4_4)
- Malik, A., Heyman-Schrum, C., & Johri, A. (2019). Use of Twitter across educational settings: a review of the literature. *International Journal of Educational Technology in Higher Education*, 16(1), 36. <https://doi.org/10.1186/s41239-019-0166-x>
- McCallum, A., & Nigam, K. (1998). A comparison of event models for naive bayes text classification. *AAAI Conference on Artificial Intelligence*. <https://api.semanticscholar.org/CorpusID:7311285>
- Muhammad, P. F., Kusumaningrum, R., & Wibowo, A. (2021). Sentiment Analysis Using Word2vec And Long Short-Term Memory (LSTM) For Indonesian Hotel Reviews. *Procedia Computer Science*, 179, 728–735. <https://doi.org/https://doi.org/10.1016/j.procs.2021.01.061>
- Parveen, H., & Pandey, S. (2016). Sentiment analysis on Twitter Data-set using Naive Bayes algorithm. *2016 2nd International Conference on Applied and Theoretical Computing and Communication Technology (ICATccT)*, 416–419. <https://doi.org/10.1109/ICATccT.2016.7912034>
- Ramdhani, S. L., Andreswari, R., & Hasibuan, M. A. (2018). Sentiment Analysis of Product Reviews using Naive Bayes Algorithm: A Case Study. *2018 2nd East Indonesia Conference on Computer and Information Technology (EIConCIT)*, 123–127. <https://doi.org/10.1109/EIConCIT.2018.8878528>
- Rennie, J. D. M., Shih, L., Teevan, J., & Karger, D. R. (2003). Tackling the Poor Assumptions of Naive Bayes Text Classifiers. *Proceedings of the Twentieth International Conference on International Conference on Machine Learning*, 616–623.
- Rizal, S., Adiwijaya, & Purbolaksono, M. D. (2022). Sentiment Analysis on Movie Review from Rotten Tomatoes Using Word2Vec and Naive Bayes. *2022 1st International Conference on Software Engineering and Information Technology (ICoSEIT)*, 180–185. <https://doi.org/10.1109/ICoSEIT55604.2022.10030009>
- Santoso, J., Soetiono, A. D. B., Gunawan, Setyati, E., Yuniarno, E. M., Hariadi, M., & Purnomo, M. H. (2018). Self-Training Naive Bayes Berbasis Word2Vec untuk Kategorisasi Berita Bahasa Indonesia. *Jurnal Nasional Teknik Elektro Dan Teknologi Informasi*, 7(2). <https://jurnal.ugm.ac.id/v3/JNTETI/article/view/2765>
- Sari, E. Y., Wierfi, A. D., & Setyanto, A. (2019). Sentiment Analysis of Customer Satisfaction on Transportation Network Company Using Naive Bayes Classifier. *2019 International Conference on Computer Engineering, Network, and Intelligent Multimedia (CENIM)*, 1–6. <https://doi.org/10.1109/CENIM48368.2019.8973262>
- Sato, N., Komiyama, K., Fujimoto, K., & Kotani, Y. (2011). Categorization of product pages depending on information on the Web. *2011 Eighth International Joint Conference on Computer Science and Software Engineering (JCSSE)*, 393–398. <https://doi.org/10.1109/JCSSE.2011.5930153>
- Saud, S., Jamil, B., Upadhyay, Y., & Irshad, K. (2020). Performance improvement of empirical models for estimation of global solar radiation in India: A k-fold cross-validation approach. *Sustainable Energy Technologies and Assessments*, 40, 100768. <https://doi.org/https://doi.org/10.1016/j.seta.2020.100768>

- Schütze, H., Manning, C. D., & Raghavan, P. (2008). *Introduction to information retrieval* (Vol. 39). Cambridge University Press Cambridge.
- Shamantha, R. B., Shetty, S. M., & Rai, P. (2019). Sentiment Analysis Using Machine Learning Classifiers: Evaluation of Performance. *2019 IEEE 4th International Conference on Computer and Communication Systems (ICCCS)*, 21–25. <https://doi.org/10.1109/CCOMS.2019.8821650>
- Wongkar, M., & Angdresey, A. (2019). Sentiment Analysis Using Naive Bayes Algorithm Of The Data Crawler: Twitter. *2019 Fourth International Conference on Informatics and Computing (ICIC)*, 1–5. <https://doi.org/10.1109/ICIC47613.2019.8985884>
- Xu, J., Zhang, Y., & Miao, D. (2020). Three-way confusion matrix for classification: A measure driven view. *Information Sciences*, *507*, 772–794. <https://doi.org/https://doi.org/10.1016/j.ins.2019.06.064>
- Yang, F.-J. (2018). An Implementation of Naive Bayes Classifier. *2018 International Conference on Computational Science and Computational Intelligence (CSCI)*, 301–306. <https://doi.org/10.1109/CSCI46756.2018.00065>
- Zeng, G. (2020). On the confusion matrix in credit scoring and its analytical properties. *Communications in Statistics - Theory and Methods*, *49(9)*, 2080–2093. <https://doi.org/10.1080/03610926.2019.1568485>